# Original Metal<sup>TM</sup> Snow Guard Specifications

To be used with the Original Metal<sup>TM</sup> Snow Guard

#### PART 1 - GENERAL

### 1.1 SUMMARY:

### A. WORK INCLUDES:

- 1. Snow guards for slate, shingle, tile and standing seam metal roofs.
- 2. Mechanically fastened, adhered or soldered attachment system.
- 3. Provide metal snow guard for the roof system.

#### **B. RELATED SECTIONS:**

- 1. Division 1: General Requirements
- 2. Division 7: Thermal and Moisture Protection
  - a. Section 07310: Shingles
  - b. Section 07320: Roof Tiles
  - c. Section 07410: Performed Metal Roofing
  - d. Section 07600: Flashing and Sheet Metal
  - e. Section 07610: Sheet Metal Roofing

#### 1.2 SYSTEM DESCRIPTION:

#### A. COMPONENTS:

1. Original Metal™ Snow Guard

### B. DESIGN REOUIREMENTS:

- 1. Spacing to be recommended by an Architect and/or Engineer.
- 2. Spacing will vary based on several factors including geographical region, snow load and building characteristics.
- 3. Our office does not perform an independent site inspection and strongly recommends that an Architect and/or Engineer review the project and any contemplated snow retention layout to ascertain and confirm the projected loads applicable to this project.

#### 1.3 SUBMITTAL:

### A. REVIEW OF SUBMITTALS:

- 1. Show locations of the snow retention system on the roof plan and specify snow guard spacing as required by an Architect and/or Engineer.
- 2. Include detailed product cut sheets, installation instructions and specifications.

# 1.4 QUALITY ASSURANCE:

## A. CERTIFICATION:

- 1. Sno Gem® strongly recommends that these products be installed by a qualified Roofing Contractor who will have the knowledge and ability to properly install the product.
- 2. Install the snow retention system in accordance with an approved layout, installation instructions and approved submittals.

### 1.5 DELIVERY / STORAGE / HANDLING:

### A. PROCEDURE:

### Raising the Bar in Snow Retention

- 1. Inspect material upon delivery and provide notice of any missing or defective items within 24 hours.
- 2. Adequately secure and protect the material until installation.

### **PART 2 - PRODUCTS**

### 2.1 MANUFACTURER:

#### ORIGINAL METAL<sup>TM</sup>:

1. A division of Sno Gem, Inc., 4800 Metalmaster Way, McHenry, IL 60050, (888) 766-4367, <a href="https://www.snogem.com">www.snogem.com</a>

### **2.2 MATERIALS:**

#### A. COMPONENTS:

1. Original Metal<sup>TM</sup> Snow Guard: Copper, Stainless Steel, Terne Metal, Prefinished Steel / Aluminum, Lead-Coated Copper, Galvalume, Freedom Gray and Zinc

#### **2.3 FINISH:**

#### A. MATERIALS:

1. Available in any standard or custom pre-finished color.

### **PART 3 - EXECUTION**

#### 3.1 EXAMINATION:

### A. SUBSTRATE:

1. Inspect the roof system in its entirety to verify proper attachment, completion and the ability of the building structure to withstand additional loading applied by the snow retention system.

# 3.2 INSTALLATION:

#### A. PROCEDURE:

1. Install the snow retention system in accordance with an approved layout, installation instructions and approved submittals.

#